

# S-17A



▶ FEATURES

- Smart exterior with exceptional strength
- Foldable small footprint stand
- NeoV Optical Filter™
- Dual digital and analog inputs
- Crisp 500 contrast ratio
- Wide 170° viewing angle
- Auto-adjustment for optimal setting
- Easy-to-use OSD
- Kensington® security slot
- VESA standard wall or arm mount



▶ SPECIFICATION

Panel	<b>Panel Type</b>	TFT LCD	
	<b>Panel Size</b>	17.0" (432mm)	
	<b>Max. Resolution</b>	SXGA 1280 x 1024	
	<b>Pixel Pitch</b>	0.264mm	
	<b>Brightness</b>	250cd/m <sup>2</sup> (Typical)	
	<b>Contrast Ratio</b>	500:1 (Typical)	
	<b>Surface Treatments</b>	Hard Coating (3H), Anti-glare Treatment	
	<b>Viewing Angle (H/V)</b>	170°/170° (Typical)	
	<b>Display Color</b>	16.7M	
	<b>Response Time (R/F)</b>	15ms/10ms (Typical)	
Input	<b>Frequency (H/V)</b>	H: 24kHz - 80kHz V: 50kHz - 75kHz	
	<b>Max. Pixel Clock</b>	135MHz	
Connector	<b>Life Time</b>	50,000hrs (Minimum)	
	<b>Analog</b>	15-Pin D-Sub	
NeoV Optical Filter	<b>Digital (DVI-D)</b>	29-Pin DVI	
	<b>Power</b>	3-Pin AC Plug	
Thickness	<b>Thickness</b>	3.0mm (0.18")	
	<b>Reflection Rate</b>	<1%	
	<b>Transmission Rate</b>	>96%	
	<b>Hardness</b>	>6H (MOH's Rating)	
Tilt	<b>Tilt</b>	+5° ~ +25°	
Mounting	<b>VESA FPMPMI</b>	Yes (100mm)	
Regulation Approval	<b>Safety &amp; EMI</b>	UL/CUL, TUV/BAURT, NORDIC, CB, ISO 13406-2, TCO 95, FCC, CE, BSMI, GOST, VCCI	
	<b>VESA</b>	DDC 1/2B, DPMS	
Power	<b>Power AC Consumption</b>	100 - 240V, 50 - 60Hz <55W (On) <5W (Stand-by) <5W (Off)	
	<b>Dimensions</b>	<b>Net (W x H x D)</b>	436 x 426 x 200mm (17.2" x 16.8" x 7.9")
		<b>Packing (W x H x D)</b>	550 x 576 x 220mm (21.7" x 22.7" x 8.7")
Weight	<b>Net Weight</b>	8.2Kg (18.0lbs)	
	<b>Gross Weight</b>	11.0Kg (24.3lbs)	
Packing	<b>1 Pallet</b>	24 Cartons	
	<b>20' Container</b>	288 Sets	
	<b>40' Container</b>	624 Sets	

\* All specifications are subject to change without prior notice.